

外形编号	CE10	CE15	CE53S
安装方式	● 非埋	● 非埋	● 非埋



输出方式	NPN NO	CE10SN13DNO	CE15SN26DNO	CE53SN08MNO
	NPN NC	CE10SN13DNC	CE15SN26DNC	CE53SN08MNC
输出方式	PNP NO	CE10SN13DPO	CE15SN26DPO	CE53SN08MPO
	PNP NC	CE10SN13DPC	CE15SN26DPC	CE53SN08MPC

### 技术参数

电源电压		10...30 VDC	10...30 VDC	18...36 VDC
负载电流		<200mA	<200mA	<250mA
压降		<2.5V	<2.5V	<2.5V
消耗电流		<15mA	<15mA	<100mA
回差范围		3...20%	3...20%	3...20%
重复精度		<3%	<3%	<3%
开关频率		60Hz	60Hz	60Hz
输出指示		黄色 LED	黄色 LED	红色 LED
适用管道	材质	非金属	非金属	...
	外径	Φ8...Φ11	Φ12...Φ26	...
	壁厚	<1mm	<1mm	...
极性保护		yes	yes	yes
短路保护		yes	yes	yes
环境温度		-10...+55°C	-10...+55°C	0...+60°C
环境湿度		35...95%	35...95%	35...95%
防护等级		IP67	IP67	IP54
外壳材料		PBT	PBT	PA66感应头/铁氟龙/不锈钢
连接方式		2m PVC 电缆	2m PVC 电缆	2m PVC 电缆
产品认证		CE	CE	CE

